

# TT PRO 315



Inline mixed-flow fans

- Maximum airflow: 2050
- Sound pressure level LpA at 3 m: 52
- Motor type: AC
- Impeller type: Mixed
- Casing material: Plastic
- Installation in any position

	Unit of measurement	TT PRO 315	
Connected air duct size	mm	315	
Speed	-	2	
Minimum supply voltage	V	230	
Maximum supply voltage	V	230	
Power supply frequency	Hz	50/60	
Rated power	W	230	320
Unit current	A	1.0	1.42
Maximum airflow	m <sup>3</sup> /h	1570	2050
Sound pressure level LpA at 3 m	dB(A)	41	52
Weight	kg	11.95	
Transported air temperature (max)	°C	60	
Ingress protection rating	-	IPX4	
Ingress protection rating of the drive	-	IPX4	
ErP compliance	-	2016	
Unit category	-	NRVU	
Type of drive installed	-	External MSD or VSD	
Type of heat recovery system	-	None	
Nominal flow rate	m <sup>3</sup> /s	0.277	
Nominal external pressure	Pa	392	
Maximum external leakage rates	%	2.7	
Static efficiency	%	33.3	

Declared typology	-	NRVU UVU
Sound power level	dB(A)	74
Effective electric power input	kW	0.332

## Dimensions

$\varnothing D$	B	H	L
310	362	408	445

