

# TT Silent-M 100 TR1V



Mixed-flow inline fans in sound-insulated casings

- Maximum airflow: 240
- Sound pressure level LpA at 3 m: 29
- Sound insulation
- Motor type: AC
- Control: Built-in speed controller
- Impeller type: Mixed-flow
- Casing material: Polypropylene/Thermoplastic elastomer
- Installation in any position
- Cable with mains plug
- Timer: Turn off timer

|  | Unit of measurement | TT Silent-M 100 TR1V |      |
|--|---------------------|----------------------|------|
| Connected air duct size                | mm                  | 100                  |      |
| Speed                                  | -                   | 2                    |      |
| Minimum supply voltage                 | V                   | 230                  |      |
| Maximum supply voltage                 | V                   | 230                  |      |
| Power supply frequency                 | Hz                  | 50/60                |      |
| Rated power                            | W                   | 24                   | 26   |
| Unit current                           | A                   | 0.1                  | 0.11 |
| Maximum airflow                        | m <sup>3</sup> /h   | 170                  | 240  |
| Sound pressure level LpA at 3 m        | dB(A)               | 24                   | 29   |
| Weight                                 | kg                  | 4.6                  |      |
| Transported air temperature (max)      | °C                  | 60                   |      |
| Ingress protection rating              | -                   | IPX4                 |      |
| Ingress protection rating of the drive | -                   | IPX4                 |      |

## Dimensions

| $\varnothing D$ | <b>B</b> | <b>B1</b> | <b>L</b> | <b>H</b> |
|-----------------|----------|-----------|----------|----------|
| 98              | 215      | 243       | 505      | 237      |

