

TT Silent-M 125 R1



Inline mixed-flow fans in sound- and heat-insulated casing

- Maximum airflow: 340
- Sound pressure level LpA at 3 m: 28
- Sound insulation
- Motor type: AC
- Impeller type: Mixed-flow
- Casing material: Coated steel
- Installation in any position
- Cable with mains plug

| | Unit of measurement | TT Silent-M 125 R1 | |
|--|---------------------|--------------------|------|
| Connected air duct size | mm | 125 | |
| Speed | - | 2 | |
| Minimum supply voltage | V | 230 | |
| Maximum supply voltage | V | 230 | |
| Power supply frequency | Hz | 50/60 | |
| Rated power | W | 25 | 29 |
| Unit current | A | 0.11 | 0.13 |
| Maximum airflow | m ³ /h | 230 | 340 |
| Sound pressure level LpA at 3 m | dB(A) | 23 | 28 |
| Weight | kg | 4.6 | |
| Transported air temperature (max) | °C | 60 | |
| Ingress protection rating | - | IPX4 | |
| Ingress protection rating of the drive | - | IPX4 | |

Dimensions

| ØD | B | B1 | L | H |
|-----|-----|-----|-----|-----|
| 123 | 215 | 243 | 474 | 237 |

