

# TT Silent-M 160 TR1

Inline mixed-flow fans in sound- and heat-insulated casing



- Maximum airflow: 555
- Sound pressure level LpA at 3 m: 33
- Sound insulation
- Motor type: AC
- Impeller type: Mixed-flow
- Casing material: Polypropylene/Thermoplastic elastomer
- Installation in any position
- Cable with mains plug
- Timer: Turn off timer

|  | Unit of measurement | TT Silent-M 160 TR1 |      |
|--|---------------------|---------------------|------|
| Connected air duct size                | mm                  | 160                 |      |
| Speed                                  | -                   | 2                   |      |
| Minimum supply voltage                 | V                   | 230                 |      |
| Maximum supply voltage                 | V                   | 230                 |      |
| Power supply frequency                 | Hz                  | 50/60               |      |
| Rated power                            | W                   | 45                  | 52   |
| Unit current                           | A                   | 0.2                 | 0.23 |
| Maximum airflow                        | m <sup>3</sup> /h   | 405                 | 555  |
| Sound pressure level LpA at 3 m        | dB(A)               | 26                  | 33   |
| Weight                                 | kg                  | 6.1                 |      |
| Transported air temperature (max)      | °C                  | 60                  |      |
| Ingress protection rating              | -                   | IPX4                |      |
| Ingress protection rating of the drive | -                   | IPX4                |      |

## Dimensions

| ØD  | B   | B1  | L   | H   |
|-----|-----|-----|-----|-----|
| 157 | 247 | 274 | 580 | 260 |

