

TT Silent-M 160 TV



Inline mixed-flow fans in sound- and heat-insulated casing

- Maximum airflow: 555
- Sound pressure level LpA at 3 m: 33
- Sound insulation
- Motor type: AC
- Control: Built-in speed controller
- Impeller type: Mixed-flow
- Casing material: Polypropylene/Thermoplastic elastomer
- Installation in any position
- Timer: Turn off timer

| | Unit of measurement | TT Silent-M 160 TV | |
|--|---------------------|--------------------|------|
| Connected air duct size | mm | 160 | |
| Speed | - | 2 | |
| Minimum supply voltage | V | 230 | |
| Maximum supply voltage | V | 230 | |
| Power supply frequency | Hz | 50/60 | |
| Rated power | W | 45 | 52 |
| Unit current | A | 0.2 | 0.23 |
| Maximum airflow | m ³ /h | 405 | 555 |
| Sound pressure level LpA at 3 m | dB(A) | 26 | 33 |
| Weight | kg | 6.1 | |
| Transported air temperature (max) | °C | 60 | |
| Ingress protection rating | - | IPX4 | |
| Ingress protection rating of the drive | - | IPX4 | |

Dimensions

| ØD | B | B1 | L | H |
|-----|-----|-----|-----|-----|
| 157 | 247 | 274 | 580 | 260 |

