


TT Silent-M 200



Inline mixed-flow fans in sound- and heat-insulated casing


- Maximum airflow: 1020
- Sound pressure level LpA at 3 m: 36
- Sound insulation
- Motor type: AC
- Impeller type: Mixed-flow
- Casing material: Coated steel
- Installation in any position

	Unit of measurement	TT Silent-M 200		
Connected air duct size	mm	200		
Speed	-	3		
Minimum supply voltage	V	230		
Maximum supply voltage	V	230		
Power supply frequency	Hz	50/60		
Rated power	W	82	100	110
Unit current	A	0.37	0.44	0.49
Maximum airflow	m³/h	731	961	1020
Sound pressure level LpA at 3 m	dB(A)	30	34	36
Weight	kg	8		
Transported air temperature (max)	°C	60		
Ingress protection rating	-	IPX4		
Ingress protection rating of the drive	-	IPX4		




Dimensions

ØD	B	B1	L	H
198	293	386	550	295



Ecodesign



Trademark	Vents		
Model	TT Silent-M 200		
Specific energy consumption (SEC) (kWh/(m ² /a))	Cold	Average	Warm
-52.8	A+	-25.7	C -10.2 E
Type of ventilation unit	Unidirectional		
Type of drive installed	Multi-speed		
Type of heat recovery system	None		
Maximum flow rate (m ³ /h)	800		
Electric power input (W)	110		
Reference flow rate (m ³ /s)	0.156		
Reference pressure difference (Pa)	50		
Specific power input (SPI) (W/(m ³ /h))	0.139		
Control typology	Local demand control		
Maximum external leakage rates (%)	2.7		
Declared typology	RVU UVU		
Sound power level (dB(A))	33		
The annual electricity consumption (AEC) (kWh/a)	Cold	Average	Warm
104	104	104	104
The annual heating saved (AHS) (kWh/a)	Cold	Average	Warm
5536	2830	1280	