

# TT Silent-M 200 R1



Inline mixed-flow fans in sound- and heat-insulated casing

- Maximum airflow: 1020
- Sound pressure level LpA at 3 m: 36
- Sound insulation
- Motor type: AC
- Impeller type: Mixed-flow
- Casing material: Polypropylene/Thermoplastic elastomer
- Installation in any position
- Cable with mains plug

|  | Unit of measurement | TT Silent-M 200 R1 |      |      |
|--|---------------------|--------------------|------|------|
| Connected air duct size                | mm                  | 200                |      |      |
| Speed                                  | -                   | 3                  |      |      |
| Minimum supply voltage                 | V                   | 230                |      |      |
| Maximum supply voltage                 | V                   | 230                |      |      |
| Power supply frequency                 | Hz                  | 50/60              |      |      |
| Rated power                            | W                   | 82                 | 100  | 110  |
| Unit current                           | A                   | 0.37               | 0.44 | 0.49 |
| Maximum airflow                        | m <sup>3</sup> /h   | 731                | 961  | 1020 |
| Sound pressure level LpA at 3 m        | dB(A)               | 30                 | 34   | 36   |
| Weight                                 | kg                  | 8                  |      |      |
| Transported air temperature (max)      | °C                  | 60                 |      |      |
| Ingress protection rating              | -                   | IPX4               |      |      |
| Ingress protection rating of the drive | -                   | IPX4               |      |      |

## Dimensions

| ØD  | B   | B1  | L   | H   |
|-----|-----|-----|-----|-----|
| 198 | 293 | 386 | 550 | 295 |

