

TT Silent-M 200 TR1V



Inline mixed-flow fans in sound- and heat-insulated casing

- Maximum airflow: 1020
- Sound pressure level LpA at 3 m: 36
- Sound insulation
- Motor type: AC
- Control: Built-in speed controller
- Impeller type: Mixed-flow
- Casing material: Polypropylene/Thermoplastic elastomer
- Installation in any position
- Cable with mains plug
- Timer: Turn off timer

| | Unit of measurement | TT Silent-M 200 TR1V | | |
|--|---------------------|----------------------|------|------|
| Connected air duct size | mm | 200 | | |
| Speed | - | 3 | | |
| Minimum supply voltage | V | 230 | | |
| Maximum supply voltage | V | 230 | | |
| Power supply frequency | Hz | 50/60 | | |
| Rated power | W | 82 | 100 | 110 |
| Unit current | A | 0.37 | 0.44 | 0.49 |
| Maximum airflow | m ³ /h | 731 | 961 | 1020 |
| Sound pressure level LpA at 3 m | dB(A) | 30 | 34 | 36 |
| Weight | kg | 8 | | |
| Transported air temperature (max) | °C | 60 | | |
| Ingress protection rating | - | IPX4 | | |
| Ingress protection rating of the drive | - | IPX4 | | |

Dimensions

| $\varnothing D$ | B | B1 | L | H |
|-----------------|-----|-----|-----|-----|
| 198 | 293 | 386 | 550 | 295 |

