

TT Silent-M 250 TR1V



Inline mixed-flow fans in sound- and heat-insulated casing

- Maximum airflow: 1400
- Sound pressure level LpA at 3 m: 38
- Sound insulation
- Motor type: AC
- Control: Built-in speed controller
- Impeller type: Mixed-flow
- Casing material: Polypropylene/Thermoplastic elastomer
- Installation in any position
- Cable with mains plug
- Timer: Turn off timer

| | Unit of measurement | TT Silent-M 250 TR1V | |
|--|---------------------|----------------------|------|
| Connected air duct size | mm | 250 | |
| Speed | - | 2 | |
| Minimum supply voltage | V | 230 | |
| Maximum supply voltage | V | 230 | |
| Power supply frequency | Hz | 50/60 | |
| Rated power | W | 125 | 177 |
| Unit current | A | 0.54 | 0.79 |
| Maximum airflow | m ³ /h | 1110 | 1400 |
| Sound pressure level LpA at 3 m | dB(A) | 34 | 38 |
| Weight | kg | 15 | |
| Transported air temperature (max) | °C | 60 | |
| Ingress protection rating | - | IPX4 | |
| Ingress protection rating of the drive | - | IPX4 | |

Dimensions

| $\varnothing D$ | B | B1 | L | H |
|-----------------|----------|-----------|----------|----------|
| 248 | 358 | 445 | 658 | 360 |

