

# TT Silent-M 315 T



Inline mixed-flow fans in sound- and heat-insulated casing

- Maximum airflow: 2050
- Sound pressure level LpA at 3 m: 40
- Sound insulation
- Motor type: AC
- Impeller type: Mixed-flow
- Casing material: Polypropylene/Thermoplastic elastomer
- Installation in any position
- Timer: Turn off timer

|  | Unit of measurement | TT Silent-M 315 T |      |
|--|---------------------|-------------------|------|
| Connected air duct size                | mm                  | 315               |      |
| Speed                                  | -                   | 2                 |      |
| Minimum supply voltage                 | V                   | 230               |      |
| Maximum supply voltage                 | V                   | 230               |      |
| Power supply frequency                 | Hz                  | 50/60             |      |
| Rated power                            | W                   | 230               | 320  |
| Unit current                           | A                   | 1                 |      |
| Maximum airflow                        | m <sup>3</sup> /h   | 1570              | 2050 |
| Sound pressure level LpA at 3 m        | dB(A)               | 36                | 40   |
| Weight                                 | kg                  | 25                |      |
| Transported air temperature (max)      | °C                  | 60                |      |
| Ingress protection rating              | -                   | IPX4              |      |
| Ingress protection rating of the drive | -                   | IPX4              |      |

## Dimensions

| ØD  | B   | B1  | L   | H   |
|-----|-----|-----|-----|-----|
| 313 | 432 | 520 | 780 | 434 |

