

# VCN 125



Exhaust centrifugal fans in steel casing for outdoor surface mounting

- Maximum airflow: 485
- Sound pressure level LpA at 3 m: 54
- Motor type: AC
- Impeller type: Centrifugal backward curved blades
- Casing material: Coated steel
- Installation in any position

	Unit of measurement	VCN 125
Connected air duct size	mm	125
Speed	-	1
Minimum supply voltage	V	230
Maximum supply voltage	V	230
Power supply frequency	Hz	50/60
Rated power	W	75
Unit current	A	0.33
Maximum airflow	m <sup>3</sup> /h	485
Sound pressure level LpA at 3 m	dB(A)	54
Weight	kg	3.82
Transported air temperature (max)	°C	55
Ingress protection rating	-	IPX4
Ingress protection rating of the drive	-	IP44
ErP compliance	-	2016, 2018
Cold - Specific energy consumption (SEC)	kWh/(m <sup>3</sup> /a)	53.4
SEC Class Cold	-	A+
Average - Specific energy consumption (SEC)	kWh/(m <sup>3</sup> /a)	26.4
SEC Class Average	-	B
Warm - Specific energy consumption (SEC)	kWh/(m <sup>3</sup> /a)	10.9
SEC Class Warm	-	E
Unit category	-	RVU

Type of ventilation unit	-	Unidirectional
Type of drive installed	-	Variable speed
Type of heat recovery system	-	None
Maximum flow rate	m <sup>3</sup> /h	325
Electric power input	W	60
Reference flow rate	m <sup>3</sup> /s	0.063
Reference pressure difference	Pa	50
Specific power input (SPI)	W/(m <sup>3</sup> /h)	0.145
Control typology	-	Local demand control
Maximum external leakage rates	%	2.7
Cold - The annual electricity consumption (AEC)	kWh/a	77
Average - The annual electricity consumption (AEC)	kWh/a	77
Warm - Jährlicher Stromverbrauch (JSV)	kWh/a	77
Cold - The annual heating saved (AHS)	kWh/a	5536
The annual heating saved (AHS) Average	kWh/a	2830
The annual heating saved (AHS) Warm	kWh/a	1280
Declared typology	-	RVU UVU
Sound power level	dB(A)	54

## Dimensions

ØD	B	H	L
124	260	355	138

