



VCU 4E 200x102



Radial fans


- Maximum airflow: 1350
- Sound pressure level LpA at 3 m: 65
- Motor type: AC
- Impeller type: Centrifugal forward curved blades
- Casing material: Polypropylene/Thermoplastic elastomer

	Unit of measurement	VCU 4E 200x102
Speed	-	1
Minimum supply voltage	V	230
Maximum supply voltage	V	230
Power supply frequency	Hz	50
Rated power	W	280
Unit current	A	1.25
Maximum airflow	m ³ /h	1350
Sound pressure level LpA at 3 m	dB(A)	65
Weight	kg	8
Transported air temperature (max)	°C	40
Transported air temperature (min)	°C	-25
Ingress protection rating	-	IPX4
Ingress protection rating of the drive	-	IP44











Dimensions

ØD	B	H	H1	H2	L	L1	L2	P	M	d
200	345	398	165	134	152	175	143	185	240	9



Accessories

Speed controllers





Name	Photo	Description
RS-1-300		Speed controller
RS-1-400		Speed controller
RS-1.5 N		Speed controller
RS-1.5 V		Speed controller
RS-2 N		Speed controller
RS-2 V		Speed controller
RS-2.5 N		Speed controller
RS-2.5 V		Speed controller

RS-1,5-PS		Used in ventilation systems for switching on/off and speed control of single-phase fan motors with voltage control
RS-2,5-PS		Used in ventilation systems for switching on/off and speed control of single-phase fan motors with voltage control
RS-4,0-PS		Used in ventilation systems for switching on/off and speed control of single-phase fan motors with voltage control
RS-3,0-T		Applied in ventilation systems for speed switching ON/OFF and speed control of single-phase power-controlled motors
RS-5,0-T		Applied in ventilation systems for speed switching ON/OFF and speed control of single-phase power-controlled motors
RS-10,0-T		Applied in ventilation systems for speed switching ON/OFF and speed control of single-phase power-controlled motors
RS-3,0-TA		Applied in ventilation systems for switching ON/OFF and speed controlling of single-phase power-controlled motors
RS-5,0-TA		Applied in ventilation systems for switching ON/OFF and speed controlling of single-phase power-controlled motors
RS-10,0-TA		Applied in ventilation systems for switching ON/OFF and speed controlling of single-phase power-controlled motors
RSA5E-2-P		Speed control enables not only selecting the comfortable ventilation mode for the periodically visited premises but reducing the energy consumption for the ventilation
RSA5E-2-M		Speed controls enables not only selecting the comfortable ventilation mode for the periodically visited premises but reducing the energy consumption for the ventilation
RSA5E-3-M		Speed controls enables not only selecting the comfortable ventilation mode for the periodically visited premises but reducing the energy consumption for the ventilation
RSA5E-4-M		Speed controls enables not only selecting the comfortable ventilation mode for the periodically visited premises but reducing the energy consumption for the ventilation
RSA5E-3,5-T		Speed controllers are applied for air flow control of single phase fans by means of motor step speed control
RSA5E-5,0-T		Speed controllers are applied for air flow control of single phase fans by means of motor step speed control

Temperature regulators

Name	Photo	Description
RT-10		Temperature regulator

Sensors

Name	Photo	Description
T-1.5 N		Sensor
TH-1.5 N		Sensor
TF-1.5 N		Sensor
TP-1.5 N		Sensor

Ecodesign

Trademark	Vents
Model	VCU 4E 200x102
Type of drive installed	External MSD or VSD
Type of heat recovery system	None
Nominal flow rate (m ³ /s)	0.252
Nominal external pressure (Pa)	206
Maximum external leakage rates (%)	2.7
Static efficiency (%)	21
Declared typology	NRVU UVU
Effective electric power input (kW)	0.252
Sound power level (dB(A))	85