

# VCUN 160x74-0,75-2 R90

Scroll single-inlet centrifugal fans with the impeller mounted directly on the three phase asynchronous motor shaft. The fan is designed for supply and exhaust ventilation systems

- Maximum airflow: 1540
- Sound pressure level LpA at 3 m: 68
- Motor type: AC
- Impeller type: Centrifugal forward curved blades
- Casing material: Coated steel



	Unit of measurement	VCUN 160x74-0,75-2 R90
Speed	-	1
Minimum supply voltage	V	400
Maximum supply voltage	V	400
Power supply frequency	Hz	50
Rated power	W	750
Unit current	A	1.8
Maximum airflow	m <sup>3</sup> /h	1540
Sound pressure level LpA at 3 m	dB(A)	68
Weight	kg	13
Transported air temperature (max)	°C	60
Ingress protection rating	-	IP54
Ingress protection rating of the drive	-	IP54






## Dimensions

ØD	Ød	Ød1	B	H	H1	H2	H3	L	L1	L2	P	M	I	G	K	S
160	8	10	277	373	134	106	173	356	134	104	141	220	260	17	252	90



## Accessories

### Speed controllers

Name	Photo	Description
<a href="#">RSA5D-12,0-M</a>		Three phase speed controller
<a href="#">RSA5D-11,0-M</a>		Three phase speed controller
<a href="#">RSA5D-8,0-M</a>		Three phase speed controller
<a href="#">RSA5D-6,0-M</a>		Three phase speed controller
<a href="#">RSA5D-3,5-T</a>		Three phase speed controller