

# VCUN 250x127-5,5-2 R90

Scroll single-inlet centrifugal fans with the impeller mounted directly on the three phase asynchronous motor shaft. The fan is designed for supply and exhaust ventilation systems

- Maximum airflow: 4820
- Sound pressure level LpA at 3 m: 81
- Motor type: AC
- Impeller type: Centrifugal forward curved blades
- Casing material: Coated steel



	Unit of measurement	VCUN 250x127-5,5-2 R90
Speed	-	1
Minimum supply voltage	V	400
Maximum supply voltage	V	400
Power supply frequency	Hz	50
Rated power	W	5500
Unit current	A	10.7
Maximum airflow	m <sup>3</sup> /h	4820
Sound pressure level LpA at 3 m	dB(A)	81
Weight	kg	40
Transported air temperature (max)	°C	60
Ingress protection rating	-	IP54
Ingress protection rating of the drive	-	IP54

## Dimensions

ØD	Ød	Ød1	B	H	H1	H2	H3	L	L1	L2	P	M	I	G	K	S
250	10	12	431	614	202	168	312	517	202	166	213	300	397	27	355	140



## Accessories

### Speed controllers

Name	Photo	Description
<a href="#">RSA5D-12,0-M</a>		Three phase speed controller