


VK 150 EC P



Centrifugal inline fans in plastic casings with EC-motors

- Maximum airflow: 630
- Sound pressure level LpA at 3 m: 45
- Motor type: EC
- Control: Built-in speed controller
- Impeller type: Centrifugal backward curved blades
- Casing material: Polypropylene/Thermoplastic elastomer
- Installation in any position
- Cable with mains plug

| | Unit of measurement | VK 150 EC P |
|--|---------------------|-------------|
| Connected air duct size | mm | 160/150 |
| Speed | - | 1 |
| Minimum supply voltage | V | 230 |
| Maximum supply voltage | V | 230 |
| Power supply frequency | Hz | 50/60 |
| Rated power | W | 82 |
| Unit current | A | 0.63 |
| Maximum airflow | m ³ /h | 630 |
| Sound pressure level LpA at 3 m | dB(A) | 45 |
| Weight | kg | 2.5 |
| Transported air temperature (max) | °C | 60 |
| Transported air temperature (min) | °C | -25 |
| Ingress protection rating | - | IPX4 |
| Ingress protection rating of the drive | - | IP55 |



Dimensions

| ØD | ØD1 | B | L | L1 | L2 | L3 |
|-----|-----|-----|-----|----|----|----|
| 150 | 300 | 310 | 286 | 30 | 30 | 30 |

