

VK 315 EC



Inline centrifugal fans in plastic casing

- Maximum airflow: 1500
- Sound pressure level LpA at 3 m: 48
- Motor type: EC
- Impeller type: Centrifugal backward curved blades
- Casing material: Plastic
- Installation in any position

	Unit of measurement	VK 315 EC
Connected air duct size	mm	315
Speed	-	1
Minimum supply voltage	V	230
Maximum supply voltage	V	230
Power supply frequency	Hz	50/60
Rated power	W	165
Unit current	A	1.15
Maximum airflow	m ³ /h	1500
Sound pressure level LpA at 3 m	dB(A)	48
Weight	kg	4.9
Transported air temperature (max)	°C	60
Transported air temperature (min)	°C	-25
Ingress protection rating	-	IPX4
Ingress protection rating of the drive	-	IP55
ErP compliance	-	2016, 2018
Unit category	-	NRVU
Type of drive installed	-	Integrated VSD
Type of heat recovery system	-	None
Nominal flow rate	m ³ /s	0.076
Nominal external pressure	Pa	1022
Maximum external leakage rates	%	2.7

Static efficiency	%	53.3
Declared typology	-	NRVU UVU
Sound power level	dB(A)	69
Effective electric power input	kW	0.17

Dimensions

$\varnothing D$	$\varnothing D1$	B	L	L1	L2	L3
315	400	414	276	40	55	40

