

VKF 2D 300



Low pressure axial fans in the steel casing with for wall mounting

- Maximum airflow: 2310
- Sound pressure level LpA at 3 m: 52
- Motor type: AC
- Impeller type: Axial
- Casing material: Coated steel
- Installation in any position

	Unit of measurement	VKF 2D 300
Connected air duct size	mm	300
Speed	-	1
Minimum supply voltage	V	400
Maximum supply voltage	V	400
Power supply frequency	Hz	50/60
Rated power	W	145
Unit current	A	0.25
Maximum airflow	m ³ /h	2310
Sound pressure level LpA at 3 m	dB(A)	52
Weight	kg	5.7
Transported air temperature (max)	°C	60
Transported air temperature (min)	°C	-30
Ingress protection rating	-	IPX4
ErP compliance	-	N/A
Unit category	-	NRVU
Type of drive installed	-	External MSD or VSD
Type of heat recovery system	-	None
Nominal flow rate	m ³ /s	0.38
Nominal external pressure	Pa	110
Maximum external leakage rates	%	2.7
Static efficiency	%	30.2

Declared typology	-	NRVU UVU
Sound power level	dB(A)	80
Effective electric power input	kW	0.141

Dimensions

$\varnothing D$	$\varnothing D1$	$\varnothing D2$	$\varnothing d$	B	L
310	356	382	7	410	160

