


VKHz 4D 500




Centrifugal roof fans with horizontal air exhaust

- Maximum airflow: 8435
- Sound pressure level LpA at 3 m: 62
- Motor type: AC
- Impeller type: Centrifugal backward curved blades
- Casing material: Galvanized steel

| | Unit of measurement | VKHz 4D 500 |
|--|---------------------|-------------|
| Speed | - | 1 |
| Minimum supply voltage | V | 400 |
| Maximum supply voltage | V | 400 |
| Power supply frequency | Hz | 50 |
| Rated power | W | 1527 |
| Unit current | A | 2.64 |
| Maximum airflow | m ³ /h | 8435 |
| Sound pressure level LpA at 3 m | dB(A) | 62 |
| Weight | kg | 46.6 |
| Transported air temperature (max) | °C | 50 |
| Transported air temperature (min) | °C | -30 |
| Ingress protection rating | - | IPX4 |
| Ingress protection rating of the drive | - | IP54 |





Dimensions

| H | H1 | A | B | C | Ød | ØD |
|-----|-----|-----|-----|-----|----|-----|
| 490 | 530 | 710 | 700 | 535 | 11 | 438 |



Ecodesign

| Trademark | Vents |
|---------------------------------------|---------------------|
| Model | VKHz 4D 500 |
| Type of drive installed | External MSD or VSD |
| Type of heat recovery system | None |
| Nominal flow rate (m ³ /s) | 1.746 |
| Nominal external pressure (Pa) | 498 |
| Maximum external leakage rates (%) | 2.7 |
| Static efficiency (%) | 58.1 |
| Declared typology | NRVU UVU |
| Effective electric power input (kW) | 1.527 |
| Sound power level (dB(A)) | 82 |