


# VKHz 4E 355




Centrifugal roof fans with horizontal air exhaust

- Maximum airflow: 2480
- Sound pressure level LpA at 3 m: 51
- Motor type: AC
- Impeller type: Centrifugal backward curved blades
- Casing material: Galvanized steel

	Unit of measurement	VKHz 4E 355
Speed	-	1
Minimum supply voltage	V	230
Maximum supply voltage	V	230
Power supply frequency	Hz	50/60
Rated power	W	219
Unit current	A	0.96
Maximum airflow	m <sup>3</sup> /h	2480
Sound pressure level LpA at 3 m	dB(A)	51
Weight	kg	28.3
Transported air temperature (max)	°C	50
Transported air temperature (min)	°C	-25
Ingress protection rating	-	IPX4
Ingress protection rating of the drive	-	IP54





## Dimensions

H	H1	A	B	C	Ød	ØD
322	361	625	620	450	11	438



## Ecodesign

Trademark	Vents
Model	VKHz 4E 355
Type of drive installed	External MSD or VSD
Type of heat recovery system	None
Nominal flow rate (m <sup>3</sup> /s)	0.32
Nominal external pressure (Pa)	255
Maximum external leakage rates (%)	2.7
Static efficiency (%)	41.7
Declared typology	NRVU UVU
Effective electric power input (kW)	0.2
Sound power level (dB(A))	71