



VKM 250 EC Q



Inline centrifugal fans in steel casing

- Maximum airflow: 2500
- Sound pressure level LpA at 3 m: 44
- Motor type: EC
- Impeller type: Centrifugal backward curved blades
- Casing material: Coated steel
- Installation in any position

	Unit of measurement	VKM 250 EC Q
Connected air duct size	mm	250
Speed	-	1
Minimum supply voltage	V	230
Maximum supply voltage	V	230
Power supply frequency	Hz	50/60
Rated power	W	100
Unit current	A	0.74
Maximum airflow	m ³ /h	2500
Sound pressure level LpA at 3 m	dB(A)	44
Transported air temperature (max)	°C	60
Transported air temperature (min)	°C	-25
Ingress protection rating	-	IPX4
Ingress protection rating of the drive	-	IP44




Dimensions

ØD	ØD1	B	B1	H	L	L1	L2	L3
248	345	395	355	435	250	25	30	40



Ecodesign



Trademark	Vents					
Model	VKM 250 EC Q					
Specific energy consumption (SEC) (kWh/(m ² /a))	Cold		Average		Warm	
	-54.6	A+	-27.5	B	-12	E
Type of ventilation unit	Unidirectional					
Type of drive installed	Variable speed					
Type of heat recovery system	None					
Maximum flow rate (m ³ /h)	920					
Electric power input (W)	105					
Reference flow rate (m ³ /s)	0.179					
Reference pressure difference (Pa)	50					
Specific power input (SPI) (W/(m ³ /h))	0.061					
Control typology	Local demand control					
Maximum external leakage rates (%)	2.7					
Declared typology	RVU UVU					
Sound power level (dB(A))	58					
The annual electricity consumption (AEC) (kWh/a)	Cold		Average		Warm	
	32		32		32	
The annual heating saved (AHS) (kWh/a)	Cold		Average		Warm	
	5536		2830		1280	