

## VKMSz 150



Inline centrifugal fans in galvanized casing

- Maximum airflow: 710
- Sound pressure level LpA at 3 m: 48
- Motor type: AC
- Impeller type: Centrifugal backward curved blades
- Casing material: Galvanized steel
- Installation in any position

	Unit of measurement	VKMSz 150
Connected air duct size	mm	150
Speed	-	1
Minimum supply voltage	V	220
Maximum supply voltage	V	240
Power supply frequency	Hz	50/60
Rated power	W	127
Unit current	A	0.56
Maximum airflow	m <sup>3</sup> /h	710
Sound pressure level LpA at 3 m	dB(A)	48
Weight	kg	4.8
Transported air temperature (max)	°C	60
Transported air temperature (min)	°C	-25
Ingress protection rating	-	IPX4
Ingress protection rating of the drive	-	IP44
ErP compliance	-	2016, 2018
Cold - Specific energy consumption (SEC)	kWh/(m <sup>2</sup> /a)	52.6
SEC Class Cold	-	A+
Average - Specific energy consumption (SEC)	kWh/(m <sup>2</sup> /a)	25.5
SEC Class Average	-	C
Warm - Specific energy consumption (SEC)	kWh/(m <sup>2</sup> /a)	10
SEC Class Warm	-	E

Unit category	-	RVU
Type of ventilation unit	-	Unidirectional
Type of drive installed	-	Variable speed
Type of heat recovery system	-	None
Maximum flow rate	m <sup>3</sup> /h	600
Electric power input	W	126
Reference flow rate	m <sup>3</sup> /s	0.117
Reference pressure difference	Pa	50
Specific power input (SPI)	W/(m <sup>3</sup> /h)	0.21
Control typology	-	Local demand control
Maximum external leakage rates	%	2.7
Cold - The annual electricity consumption (AEC)	kWh/a	111
Average - The annual electricity consumption (AEC)	kWh/a	111
Warm - Jährlicher Stromverbrauch (JSV)	kWh/a	111
Cold - The annual heating saved (AHS)	kWh/a	5536
The annual heating saved (AHS) Average	kWh/a	2830
The annual heating saved (AHS) Warm	kWh/a	1280
Declared typology	-	RVU UVU
Sound power level	dB(A)	69

## Dimensions

ØD	ØD1	B	B1	L	L1	L2	L3
149	345	355	395	230	20	20	40

