

## VKMz 315 Q



Inline centrifugal fans in galvanized casing

- Maximum airflow: 1330
- Sound pressure level LpA at 3 m: 52
- Motor type: AC
- Impeller type: Centrifugal backward curved blades
- Casing material: Galvanized steel
- Installation in any position

	Unit of measurement	VKMz 315 Q
Connected air duct size	mm	315
Speed	-	1
Minimum supply voltage	V	220
Maximum supply voltage	V	240
Power supply frequency	Hz	50/60
Rated power	W	151
Unit current	A	0.66
Maximum airflow	m <sup>3</sup> /h	1330
Sound pressure level LpA at 3 m	dB(A)	52
Weight	kg	6.5
Transported air temperature (max)	°C	50
Transported air temperature (min)	°C	-25
Ingress protection rating	-	IPX4
Ingress protection rating of the drive	-	IP44
ErP compliance	-	2016, 2018
Unit category	-	NRVU
Type of drive installed	-	External MSD or VSD
Type of heat recovery system	-	None
Nominal flow rate	m <sup>3</sup> /s	0.204
Nominal external pressure	Pa	323
Maximum external leakage rates	%	2.7

Static efficiency	%	44.3
Declared typology	-	NRVU UVU
Sound power level	dB(A)	72
Effective electric power input	kW	0.152

## Dimensions

$\varnothing D$	$\varnothing D1$	B	B1	L	L1	L2	L3
313	402	410	450	308	33	55	40

