

VKP 600x350 M1 EC



Centrifugal fans for rectangular ducts

- Maximum airflow: 2815
- Sound pressure level LpA at 3 m: 49
- Motor type: EC
- Impeller type: Centrifugal backward curved blades
- Casing material: Galvanized steel
- Installation in any position

	Unit of measurement	VKP 600x350 M1 EC
Connected air duct size	mm	600x350
Speed	-	1
Minimum supply voltage	V	230
Maximum supply voltage	V	230
Power supply frequency	Hz	50/60
Rated power	W	361
Unit current	A	2.62
Maximum airflow	m ³ /h	2815
Sound pressure level LpA at 3 m	dB(A)	49
Weight	kg	25.2
Transported air temperature (max)	°C	50
Transported air temperature (min)	°C	-25
Ingress protection rating	-	IPX4
Ingress protection rating of the drive	-	IP54
ErP compliance	-	2016, 2018
Unit category	-	NRVU
Type of drive installed	-	Integrated VSD
Type of heat recovery system	-	None
Nominal flow rate	m ³ /s	0.335
Nominal external pressure	Pa	445
Maximum external leakage rates	%	2.7

Static efficiency	%	65.3
Declared typology	-	NRVU UVU
Sound power level	dB(A)	69
Effective electric power input	kW	0.263

Dimensions

B	B1	B2	H	H1	H2	H3	L
600	620	640	350	370	390	457	650

