


# VKPF 4E 400x200




Centrifugal inline fans with forward curved blades

- Maximum airflow: 1440
- Sound pressure level LpA at 3 m: 50
- Motor type: AC
- Impeller type: Centrifugal forward curved blades
- Casing material: Galvanized steel
- Installation in any position


	Unit of measurement	VKPF 4E 400x200
Connected air duct size	mm	400x200
Speed	-	1
Minimum supply voltage	V	230
Maximum supply voltage	V	230
Power supply frequency	Hz	50
Rated power	W	295
Unit current	A	1.32
Maximum airflow	m <sup>3</sup> /h	1440
Sound pressure level LpA at 3 m	dB(A)	50
Weight	kg	17.5
Transported air temperature (max)	°C	40
Transported air temperature (min)	°C	-25
Ingress protection rating	-	IPX4
Ingress protection rating of the drive	-	IP44





### Dimensions

<b>B</b>	<b>B1</b>	<b>B2</b>	<b>H</b>	<b>H1</b>	<b>H2</b>	<b>H3</b>	<b>L</b>
400	420	440	200	220	240	255	500



## Ecodesign

Trademark	Vents
Model	VKPF 4E 400x200
Type of drive installed	External MSD or VSD
Type of heat recovery system	None
Nominal flow rate (m <sup>3</sup> /s)	0.214
Nominal external pressure (Pa)	200
Maximum external leakage rates (%)	2.7
Static efficiency (%)	20.1
Declared typology	NRVU UVU
Effective electric power input (kW)	0.217
Sound power level (dB(A))	70