

# VKPF 4E 500x250



Inline centrifugal fans for rectangular ducts

- Maximum airflow: 1750
- Sound pressure level LpA at 3 m: 53
- Motor type: AC
- Impeller type: Centrifugal forward curved blades
- Casing material: Galvanized steel
- Installation in any position

	Unit of measurement	VKPF 4E 500x250
Connected air duct size	mm	500x250
Speed	-	1
Minimum supply voltage	V	230
Maximum supply voltage	V	230
Power supply frequency	Hz	50
Rated power	W	535
Unit current	A	2.49
Maximum airflow	m <sup>3</sup> /h	1750
Sound pressure level LpA at 3 m	dB(A)	53
Weight	kg	24
Transported air temperature (max)	°C	40
Transported air temperature (min)	°C	-20
Ingress protection rating	-	IPX4
Ingress protection rating of the drive	-	IP44
Unit category	-	NRVU
Type of drive installed	-	External MSD or VSD
Type of heat recovery system	-	None
Nominal flow rate	m <sup>3</sup> /s	0.29
Nominal external pressure	Pa	286
Maximum external leakage rates	%	2.7
Static efficiency	%	24.2

Declared typology	-	NRVU UVU
Sound power level	dB(A)	73
Effective electric power input	kW	0.35

## Dimensions

B	B1	B2	H	H1	H2	H3	L
500	520	540	250	270	290	335	640

