

# VKPF1 4E 400x200



Inline sound- and heat-insulated centrifugal fans for rectangular ducts

- Maximum airflow: 1440
- Sound pressure level LpA at 3 m: 42
- Sound insulation
- Motor type: AC
- Impeller type: Centrifugal forward curved blades
- Casing material: Galvanized steel
- Installation in any position

	Unit of measurement	VKPF1 4E 400x200
Connected air duct size	mm	400x200
Speed	-	1
Minimum supply voltage	V	230
Maximum supply voltage	V	230
Power supply frequency	Hz	50
Rated power	W	295
Unit current	A	1.32
Maximum airflow	m <sup>3</sup> /h	1440
Sound pressure level LpA at 3 m	dB(A)	42
Weight	kg	29
Transported air temperature (max)	°C	40
Transported air temperature (min)	°C	-25
Ingress protection rating	-	IPX4
Ingress protection rating of the drive	-	IP44
Unit category	-	NRVU
Type of drive installed	-	External MSD or VSD
Type of heat recovery system	-	None
Nominal flow rate	m <sup>3</sup> /s	0.214
Nominal external pressure	Pa	200
Maximum external leakage rates	%	2.7
Static efficiency	%	20.1

Declared typology	-	NRVU UVU
Sound power level	dB(A)	62
Effective electric power input	kW	0.217

## Dimensions

B	B1	B2	B3	H	H1	H2	H3	L
400	420	440	470	200	220	240	360	500

