



VKPF1 4E 400x200



Inline sound- and heat-insulated centrifugal fans for rectangular ducts

- Maximum airflow: 1440
- Sound pressure level LpA at 3 m: 42
- Sound insulation
- Motor type: AC
- Impeller type: Centrifugal forward curved blades
- Casing material: Galvanized steel
- Installation in any position

	Unit of measurement	VKPF1 4E 400x200
Connected air duct size	mm	400x200
Speed	-	1
Minimum supply voltage	V	230
Maximum supply voltage	V	230
Power supply frequency	Hz	50
Rated power	W	295
Unit current	A	1.32
Maximum airflow	m ³ /h	1440
Sound pressure level LpA at 3 m	dB(A)	42
Weight	kg	29
Transported air temperature (max)	°C	40
Transported air temperature (min)	°C	-25
Ingress protection rating	-	IPX4
Ingress protection rating of the drive	-	IP44



Dimensions

B	B1	B2	B3	H	H1	H2	H3	L
400	420	440	470	200	220	240	360	500



Ecodesign

Trademark	Vents
Model	VKPMI 4E 400x200
Type of drive installed	External MSD or VSD
Type of heat recovery system	None
Nominal flow rate (m ³ /s)	0.214
Nominal external pressure (Pa)	200
Maximum external leakage rates (%)	2.7
Static efficiency (%)	20.1
Declared typology	NRVU UVU
Sound power level (dB(A))	62
Effective electric power input (kW)	0.217