



# VKPI 600x300 M1 EC

Centrifugal inline fans with backward curved blades in sound-insulated casings with EC-motors



- Maximum airflow: 2545
- Sound pressure level LpA at 3 m: 34
- Sound insulation
- Motor type: EC
- Impeller type: Centrifugal backward curved blades
- Casing material: Galvanized steel
- Installation in any position

	Unit of measurement	VKPI 600x300 M1 EC
Connected air duct size	mm	600x300
Speed	-	1
Minimum supply voltage	V	230
Maximum supply voltage	V	230
Power supply frequency	Hz	50/60
Rated power	W	326
Unit current	A	2.45
Maximum airflow	m <sup>3</sup> /h	2545
Sound pressure level LpA at 3 m	dB(A)	34
Weight	kg	52.9
Transported air temperature (max)	°C	50
Transported air temperature (min)	°C	-25
Ingress protection rating	-	IPX4
Ingress protection rating of the drive	-	IP54



## Dimensions

B	B1	B3	H	H1	H3	L	F	K
600	620	783	300	320	574	752	755	450



## Ecodesign

Trademark	Vents
Model	VKPI 600x300 M1 EC
Type of drive installed	Integrated VSD
Type of heat recovery system	None
Nominal flow rate (m <sup>3</sup> /s)	0.301
Nominal external pressure (Pa)	390
Maximum external leakage rates (%)	2.7
Static efficiency (%)	54.8
Declared typology	NRVU UVU
Effective electric power input (kW)	0.247
Sound power level (dB(A))	54