



VKV 4E 400



Roof centrifugal fans with vertical air discharge

- Maximum airflow: 3950
- Sound pressure level LpA at 3 m: 55
- Motor type: AC
- Impeller type: Centrifugal backward curved blades
- Casing material: Polypropylene/Thermoplastic elastomer

	Unit of measurement	VKV 4E 400
Speed	-	1
Minimum supply voltage	V	230
Maximum supply voltage	V	230
Power supply frequency	Hz	50
Rated power	W	457
Unit current	A	2
Maximum airflow	m ³ /h	3950
Sound pressure level LpA at 3 m	dB(A)	55
Weight	kg	35
Transported air temperature (max)	°C	60
Transported air temperature (min)	°C	-30
Ingress protection rating	-	IPX4
Ingress protection rating of the drive	-	IP54



Dimensions

A	B	C	ØD
738	598	375	438



Ecodesign

Trademark	Vents
Model	VKV 4E 400
Type of drive installed	External MSD or VSD
Type of heat recovery system	None
Nominal flow rate (m ³ /s)	0.728
Nominal external pressure (Pa)	131
Maximum external leakage rates (%)	2.7
Static efficiency (%)	41.6
Declared typology	NRVU UVU
Effective electric power input (kW)	0.234
Sound power level (dB(A))	73