


# VKVz 4E 450




Centrifugal roof fans with vertical air exhaust

- Maximum airflow: 6180
- Sound pressure level LpA at 3 m: 58
- Motor type: AC
- Impeller type: Centrifugal backward curved blades
- Casing material: Galvanized steel

	Unit of measurement	VKVz 4E 450
Speed	-	1
Minimum supply voltage	V	230
Maximum supply voltage	V	230
Power supply frequency	Hz	50
Rated power	W	749
Unit current	A	3.35
Maximum airflow	m <sup>3</sup> /h	6180
Sound pressure level LpA at 3 m	dB(A)	58
Weight	kg	46.6
Transported air temperature (max)	°C	60
Transported air temperature (min)	°C	-30
Ingress protection rating	-	IPX4
Ingress protection rating of the drive	-	IP54





### Dimensions

<b>A</b>	<b>B</b>	<b>C</b>	<b>ØD</b>
738	668	430	438



## Ecodesign

Trademark	Vents
Model	VKVz 4E 450
Type of drive installed	External MSD or VSD
Type of heat recovery system	None
Nominal flow rate (m <sup>3</sup> /s)	0.758
Nominal external pressure (Pa)	430
Maximum external leakage rates (%)	2.7
Static efficiency (%)	48.8
Declared typology	NRVU UVU
Effective electric power input (kW)	0.681
Sound power level (dB(A))	78