


VKVz 6D 630




Centrifugal roof fans with vertical air exhaust

- Maximum airflow: 12640
- Sound pressure level LpA at 3 m: 64
- Motor type: AC
- Impeller type: Centrifugal backward curved blades
- Casing material: Galvanized steel

| | Unit of measurement | VKVz 6D 630 |
|--|---------------------|-------------|
| Speed | - | 1 |
| Minimum supply voltage | V | 400 |
| Maximum supply voltage | V | 400 |
| Power supply frequency | Hz | 50 |
| Rated power | W | 1110 |
| Unit current | A | 2.42 |
| Maximum airflow | m ³ /h | 12640 |
| Sound pressure level LpA at 3 m | dB(A) | 64 |
| Weight | kg | 96.3 |
| Transported air temperature (max) | °C | 50 |
| Transported air temperature (min) | °C | -25 |
| Ingress protection rating | - | IPX4 |
| Ingress protection rating of the drive | - | IP54 |





Dimensions

| A | B | C | ØD |
|-----|-----|-----|-----|
| 951 | 939 | 485 | 600 |



Ecodesign

| Trademark | Vents |
|---------------------------------------|---------------------|
| Model | VKVz 6D 630 |
| Type of drive installed | External MSD or VSD |
| Type of heat recovery system | None |
| Nominal flow rate (m ³ /s) | 2.482 |
| Nominal external pressure (Pa) | 258 |
| Maximum external leakage rates (%) | 2.7 |
| Static efficiency (%) | 61.1 |
| Declared typology | NRVU UVU |
| Effective electric power input (kW) | 1.069 |
| Sound power level (dB(A)) | 84 |