

# VN-1E 80 K2



Centrifugal fans in plastic casing

- Maximum airflow: 100
- Sound pressure level LpA at 3 m: 38
- Control: Wired control panel
- Casing material: Plastic
- Backdraft protection: Backdraft damper

|                                 | Unit of measurement | VN-1E 80 K2 |      |
|---------------------------------|---------------------|-------------|------|
| Connected air duct size         | mm                  | 80          |      |
| Speed                           | -                   | 2           |      |
| Minimum supply voltage          | V                   | 220         |      |
| Maximum supply voltage          | V                   | 240         |      |
| Power supply frequency          | Hz                  | 50          |      |
| Rated power                     | W                   | 24          | 29   |
| Unit current                    | A                   | 0.11        | 0.13 |
| Maximum airflow                 | m <sup>3</sup> /h   | 75          | 100  |
| Sound pressure level LpA at 3 m | dB(A)               | 29          | 38   |
| Weight                          | kg                  | 2.7         |      |
| Ambient air temperature min     | °C                  | 1           |      |
| Ambient air temperature max     | °C                  | 40          |      |
| Ingress protection rating       | -                   | IP55        |      |

## Dimensions



## Accessories

### Speed control switches

| Name                     | Photo   | Description |
|--------------------------|---|-------------|
| <a href="#">P2-1-300</a> |   | Switch      |
| <a href="#">P2-1-300</a> |  | Switch      |