

# VNV-1E 80 KV TR



Centrifugal fan in plastic casing

- Maximum airflow: 100
- Sound pressure level LpA at 3 m: 38
- Control: Wired control panel
- Casing material: Plastic
- Backdraft protection: Backdraft damper
- Motion sensor
- Timer: Built-in

|                                 | Unit of measurement | VNV-1E 80 KV TR |      |
|---------------------------------|---------------------|-----------------|------|
| Connected air duct size         | mm                  | 80              |      |
| Speed                           | -                   | 2               |      |
| Minimum supply voltage          | V                   | 220             |      |
| Maximum supply voltage          | V                   | 240             |      |
| Power supply frequency          | Hz                  | 50              |      |
| Rated power                     | W                   | 24              | 29   |
| Unit current                    | A                   | 0.11            | 0.13 |
| Maximum airflow                 | m <sup>3</sup> /h   | 75              | 100  |
| Sound pressure level LpA at 3 m | dB(A)               | 29              | 38   |
| Weight                          | kg                  | 2.7             |      |
| Ambient air temperature min     | °C                  | 1               |      |
| Ambient air temperature max     | °C                  | 40              |      |
| Ingress protection rating       | -                   | IP55            |      |

## Dimensions



## Accessories

### Speed control switches

| Name                     | Photo  | Description |
|--------------------------|--|-------------|
| <a href="#">P2-1-300</a> |  | Switch      |

### Other accessories

| Name                  | Photo   | Description                                  |
|-----------------------|---|--|
| <a href="#">KV_80</a> |  | Plastic casing for VNV-1 80 ventilation unit |