

VPA 150-2,4-1 LCD



Supply units in the compact sound- and heat-insulated casing with electric heater

- Power of electrical reheater: 2400
- Maximum airflow: 425
- Sound pressure level LpA at 3 m: 29
- Filter: G4
- Sound insulation
- Motor type: AC
- Reheater: Electric
- Control: Remote Control
- Casing material: Galvanized steel

| | Unit of measurement | VPA 150-2,4-1 LCD |
|--|---------------------|-------------------|
| Connected air duct size | mm | 150 |
| Speed | - | 1 |
| Minimum supply voltage | V | 230 |
| Maximum supply voltage | V | 230 |
| Power supply frequency | Hz | 50 |
| Rated power | W | 98 |
| Power of electrical reheater | W | 2400 |
| Unit current | A | 10.4 |
| Maximum airflow | m ³ /h | 425 |
| Sound pressure level LpA at 3 m | dB(A) | 29 |
| Weight | kg | 52 |
| Filter | - | G4 |
| Transported air temperature (max) | °C | 55 |
| Transported air temperature (min) | °C | -25 |
| Ambient air temperature min | °C | 0 |
| Ambient air temperature max | °C | 40 |
| Ambient air humidity max | % | 80 |
| Ingress protection rating | - | IP22 |
| Ingress protection rating of the drive | - | IP44 |







Dimensions

| ØD | B | B1 | H | L | L1 |
|-----|-----|-------|-----|-----|-----|
| 149 | 455 | 496.5 | 438 | 800 | 647 |





Accessories

For round ducts

| Name | Photo | Description |
|------------------------------|---|---|
| SR 150/600 |  | Silencer is applied for noise absorption produced during the ventilating equipment operation and spread along the ducting systems |
| SR 150/900 |  | Silencer is applied for noise absorption produced during the ventilating equipment operation and spread along the ducting systems |
| SR 150/1200 |  | Silencer is applied for noise absorption produced during the ventilating equipment operation and spread along the ducting systems |
| SRF 150/600 |  | Silencer is applied for noise absorption produced during the ventilating equipment operation and spread along the ducting systems |
| SRF 150/900 |  | Silencer is applied for noise absorption produced during the ventilating equipment operation and spread along the ducting systems |
| SRF 150/2000 |  | Silencer is applied for noise absorption produced during the ventilating equipment operation and spread along the ducting systems |

For round ducts

| Name | Photo | Description |
|------|-------|-------------|
|------|-------|-------------|

| | | |
|-------------------------|---|--|
| KOM 150 |  | Spring-loaded backdraft damper for round ducts |
| KRV 150 |  | Air damper for air flow cut-off in round air ducts |

Other accessories

| Name | Photo | Description |
|-------------------------|---|-----------------------------------|
| VVG 150 |  | Flexible anti-vibration connector |

Other accessories

| Name | Photo | Description |
|------------------|---|-----------------|
| SF 397x364x70 G4 |  | Panel filter G4 |