


VS 630-6D




Centrifugal inline fans in sound-insulated casings

- Maximum airflow: 12030
- Sound pressure level LpA at 3 m: 55
- Sound insulation
- Motor type: AC
- Impeller type: Centrifugal backward curved blades
- Casing material: Polypropylene/Thermoplastic elastomer
- Installation in any position


	Unit of measurement	VS 630-6D
Connected air duct size	mm	630
Speed	-	1
Minimum supply voltage	V	400
Maximum supply voltage	V	400
Power supply frequency	Hz	50
Rated power	W	1310
Unit current	A	2.8
Maximum airflow	m ³ /h	12030
Sound pressure level LpA at 3 m	dB(A)	55
Weight	kg	98
Transported air temperature (max)	°C	60
Transported air temperature (min)	°C	-40
Ingress protection rating	-	IPX4





Dimensions

A
800



Ecodesign

Trademark	Vents
Model	VS 630-6D
Type of drive installed	External MSD or VSD
Type of heat recovery system	None
Nominal flow rate (m ³ /s)	1.923
Nominal external pressure (Pa)	270
Maximum external leakage rates (%)	2.7
Static efficiency (%)	40.5
Declared typology	NRVU UVU
Effective electric power input (kW)	1.309
Sound power level (dB(A))	75