

VS 710-6D



Inline centrifugal fans with backward curved blades in heat- and sound-insulated casing

- Maximum airflow: 15830
- Sound pressure level LpA at 3 m: 59
- Sound insulation
- Motor type: AC
- Impeller type: Centrifugal backward curved blades
- Casing material: Aluzinc
- Installation in any position

	Unit of measurement	VS 710-6D
Connected air duct size	mm	710
Speed	-	1
Minimum supply voltage	V	400
Maximum supply voltage	V	400
Power supply frequency	Hz	50
Rated power	W	2000
Unit current	A	3.9
Maximum airflow	m ³ /h	15830
Sound pressure level LpA at 3 m	dB(A)	59
Weight	kg	136
Transported air temperature (max)	°C	40
Transported air temperature (min)	°C	-20
Ingress protection rating	-	IPX4
ErP compliance	-	2016, 2018
Unit category	-	NRVU
Type of drive installed	-	External MSD or VSD
Type of heat recovery system	-	None
Nominal flow rate	m ³ /s	2.692
Nominal external pressure	Pa	376
Maximum external leakage rates	%	2.7
Static efficiency	%	50.6

Declared typology	-	NRVU UVU
Sound power level	dB(A)	79
Effective electric power input	kW	2.04

Dimensions

A
1000

