

VUE 450 P3 L A3



Heat recovery air handling units in heat- and sound-insulated casing

- Maximum airflow: 500
- Sound pressure level LpA at 3 m: 57
- Heat exchanger type: Cross flow
- Extract filter: G4
- Supply filter: G4 and F8 (PM2.5 93%)
- Sound insulation
- Motor type: AC
- Enthalpy heat exchanger
- Control: Remote Control
- Casing material: Polypropylene/Thermoplastic elastomer

	Unit of measurement	VUE 450 P3 L A3
Connected air duct size	mm	150
Speed	-	1
Minimum supply voltage	V	230
Maximum supply voltage	V	230
Power supply frequency	Hz	50
Rated power	W	354
Unit current	A	1.54
Maximum airflow	m ³ /h	500
Sound pressure level LpA at 3 m	dB(A)	57
Heat recovery efficiency, max	%	87
Heat exchanger type	-	Cross flow
Heat exchanger material	-	Enthalpy
Weight	kg	39
Extract filter	-	G4
Supply filter	-	G4 and F8 (PM2.5 93%)
Transported air temperature (max)	°C	40
Transported air temperature (min)	°C	-15
Ambient air temperature min	°C	0
Ambient air temperature max	°C	40
Ambient air humidity max	%	60
Ingress protection rating	-	IP22


Ingress protection rating of the drive

-

IP44



Dimensions

ØD	A	B	H
150	1020	704	227



Accessories


Other accessories

Name	Photo	Description
SF 300x270x48 G4		Panel filter G4
SF 300x270x48 F8		F8 panel filter

Speed control switches

Name	Photo	Description
SP3-1		Sensor speed switch

Ecodesign



Trademark	Vents					
Model	VUE 450 P3 L A3					
Specific energy consumption (SEC) (kWh/(m ² /a))	Cold	Average		Warm		
	47.9	A+	14.6	E	7.1	G
Type of ventilation unit	Bidirectional					
Type of drive installed	Variable speed					
Type of heat recovery system	Recuperative					
Thermal efficiency of heat recovery (%)	73					
Maximum flow rate (m ³ /h)	450					
Electric power input (W)	340					
Reference flow rate (m ³ /s)	0.094					
Reference pressure difference (Pa)	50					
Specific power input (SPI) (W/(m ³ /h))	0.809					
Control typology	Manual control					
Maximum internal leakage rates (%)	2.7					
Maximum external leakage rates (%)	2.7					
Declared typology	RVU BVU					
Sound power level (dB(A))	57					
The annual electricity consumption (AEC) (kWh/a)	Cold	Average		Warm		
	1595	1058		1013		
The annual heating saved (AHS) (kWh/a)	Cold	Average		Warm		
	7904	4040		1827		