

VUT 2000 H



Air handling units in the compact sound- and heat-insulated casing


- Maximum airflow: 2200
- Sound pressure level LpA at 3 m: 65
- Heat exchanger type: Cross flow
- Extract filter: G4
- Supply filter: G4
- Sound insulation
- Motor type: AC
- Control: Remote Control
- Casing material: Galvanized steel

	Unit of measurement	VUT 2000 H
Connected air duct size	mm	314
Speed	-	1
Minimum supply voltage	V	230
Maximum supply voltage	V	230
Power supply frequency	Hz	50/60
Rated power	W	1300
Unit current	A	5.68
Maximum airflow	m ³ /h	2200
Sound pressure level LpA at 3 m	dB(A)	65
Heat recovery efficiency, max	%	87
Heat exchanger type	-	Cross flow
Heat exchanger material	-	Polystyrene
Weight	kg	96
Extract filter	-	G4
Supply filter	-	G4
Transported air temperature (max)	°C	40
Transported air temperature (min)	°C	-25
Ambient air temperature min	°C	10
Ambient air temperature max	°C	50
Ambient air humidity max	%	80
Ingress protection rating	-	IP22

Ingress protection rating of the drive	-	IP44
ErP compliance	-	2016
Unit category	-	NRVU
Type of drive installed	-	Integrated MSD
Type of heat recovery system	-	Recuperative
Thermal efficiency of heat recovery	%	67
Nominal flow rate	m ³ /s	0.262
Nominal external pressure	Pa	293
Maximum internal leakage rates	%	2.7
Maximum external leakage rates	%	2.7
Static efficiency	%	32.4
Visual filter warning	-	See control panel catalogue data
Effective electric power input	kW	0.592
Face velocity at design flow rate	m/s	1.183
Sound power level	dB(A)	85
Declared typology	-	NRVU BVU
Energy performance of filters	-	B

Dimensions







ØD	B	B1	B2	B3	H	H1	H2	L	L1
313	846	796	235	588	968	360	246	1000	1050





Accessories

For round ducts



Name	Photo	Description
------	-------	-------------

SR 315/600		Silencer is applied for noise absorption produced during the ventilating equipment operation and spread along the ducting systems
SR 315/900		Silencer is applied for noise absorption produced during the ventilating equipment operation and spread along the ducting systems
SR 315/1200		Silencer is applied for noise absorption produced during the ventilating equipment operation and spread along the ducting systems
SRF 315/600		Silencer is applied for noise absorption produced during the ventilating equipment operation and spread along the ducting systems
SRF 315/900		Silencer is applied for noise absorption produced during the ventilating equipment operation and spread along the ducting systems
SRF 315/2000		Silencer is applied for noise absorption produced during the ventilating equipment operation and spread along the ducting systems

For round ducts

Name	Photo	Description
KOM 315		Spring-loaded backdraft damper for round ducts
KR 315		Air damper for air flow control in round air ducts

Other accessories

Name	Photo	Description
SF 750x295x48 G4		Panel filter G4
VL C4 300/750		Summer block