VUT 350 V1B EC A14

Vertical air handling units with a counterflow polystyrene or enthalpy heat exchanger



- Sound pressure level LpA at 3 m: 28
- Heat exchanger type: Counter flow
- Heat exchanger material: Polystyrene
- Supply filter: F7 (G4 optional)
- Extract filter: G4
- Sound-insulated casing
- Bypass: Manual
- Control: Remote Control
- Casing material: Coated steel
- Humidity sensor: Optional
- CO2 sensor: Optional
- PM2.5 sensor: Optional

	Unit of measurement	VUT 350 V1B EC A14
Connected air duct size	mm	160
Phases	-	1
Maximum supply voltage	V	230
Minimum supply voltage	V	230
Power supply frequency	Hz	50/60
Rated power	W	169
Unit current	A	1.3
Maximum airflow	m³/h	420
Rotation speed at 50hz	-	3200
Sound pressure level LpA at 3 m	dB(A)	28
Heat recovery efficiency, max	%	92
Heat exchanger type	-	Counter flow
Heat exchanger material	-	Polystyrene
Weight	kg	57
Supply filter	-	F7 (G4 optional)
Extract filter	-	G4
Transported air temperature (max)	°C	40
Transported air temperature (min)	°C	-25
Ambient air temperature min	°C	1
Ambient air temperature max	°C	40
Ingress protection rating	-	IP20

Ambient air humidity max	%	60
Ingress protection rating of the drive	-	IP44





Dimensions

ØD	B	H	L
160	470	675	730



Accessories

Sensors

Name	Photo	Description
HV2		Humidity sensor
CO2-1		CO2 sensors
CO2-2		CO2 sensors
HR-S		Electro-mechanical humidistat

Cooker Hoods

Name	Photo	Description
KH-1		Kitchen hood for removing combustion products, vapors and odors from the air

Condensation drainage

Name	Photo	Description
SH-32		Hydraulic U-trap to drain condensate from heat exchangers and coolers

For round ducts

Name	Photo	Description
KRV 160		Air dampers for automatic air flow control in round ducts

Electric actuators

Name	Photo	Description
Belimo LF230		The Belimo LF series actuators are designed for controlling air dampers with cross section up to 0.8 m² performing protection functions

Other accessories

Name	Photo	Description
SF 384x196x40 G4		Panel filter G4
SF 384x196x40 F7		F7 panel filter

Ecodesign



Trademark	Vents					
Model	VUT 350 V1B EC A14					
Specific energy consumption (SEC) (kWh/(m²/a))	Cold		Average		Warm	
	-81.2	A+	-42.5	A+	-17.7	E
Type of ventilation unit	Bidirectional					
Type of drive installed	Variable speed					
Type of heat recovery system	Recuperative					
Thermal efficiency of heat recovery (%)	86					
Maximum flow rate (m³/h)	385					
Electric power input (W)	168					
Reference flow rate (m³/s)	0.076					
Reference pressure difference (Pa)	50					
Specific power input (SPI) (W/(m³/h))	0.236					
Control typology	Local demand control					
Maximum internal leakage rates (%)	2.7					
Maximum external leakage rates (%)	2.7					
Declared typology	RVU BVU					
Sound power level (dB(A))	48					
The annual electricity consumption (AEC) (kWh/a)	Cold		Average		Warm	
	707		170		125	
The annual heating saved (AHS) (kWh/a)	Cold		Average		Warm	
	9019		4610		2085	