










Series DVUT PB EC V.2

Suspension-mounted single-room air handling units in a heat- and sound insulated casing

- Heat exchanger type: Counter flow
- Sound insulation
- Motor type: EC
- Bypass: Auto
- BMS protocol: ModBus
- Control: Smartphone
- Casing material: Galvanized steel
- Humidity sensor: Optional
- Reheater: Electric
- Preheater: Electric



Lineup	Maximum airflow, m ³ /h	Heat exchanger type	Control system	Reheater	Preheater	Control
 DVUT 300 PB EC A21 V.2	300	Counter flow	A21	×	×	Smartphone
 DVUT 300 PBE EC A21 V.2	300	Counter flow	A21	Electric	×	Smartphone
 DVUT 300 PBE2 EC A21 V.2	300	Counter flow	A21	Electric	Electric	Smartphone
 DVUT 500 PB EC A21 V.2	510	Counter flow	A21	×	×	Smartphone
 DVUT 500 PBE EC A21 V.2	510	Counter flow	A21	Electric	×	Smartphone
 DVUT 500 PBE2 EC A21 V.2	510	Counter flow	A21	Electric	Electric	Smartphone
 DVUT 1000 PB EC A21 V.2	1000	Counter flow	A21	×	×	Smartphone

 DVUT 1000 PBE EC A21 V.2	1000	Counter flow	A21	Electric	×	Smartphone
 DVUT 1000 PBE2 EC A21 V.2	1000	Counter flow	A21	Electric	Electric	Smartphone