













## Series **Enave 550 V**



Heat recovery air handling units in sound- and heat-insulated casings made of expanded polypropylene

- Heat exchanger type: Counter flow
- Sound insulation
- Motor type: EC
- Bypass: Manual
- Reheater: Optional
- Preheater: Built-in
- BMS protocol: ModBus
- Control: Wired control panel
- Casing material: EPP
- Humidity sensor: Optional
- Enthalpy heat exchanger

Lineup	Connected air duct size, mm	Rated power, W	Maximum airflow, m <sup>3</sup> /h	Service side	Control system	Reheater	Preheater	BMS protocol
 Enave 550 V A21 R	200	347	660	Right	A21	Optional	Optional	ModBus
 Enave 550 V A21 L	200	347	660	Left	A21	Optional	Optional	ModBus
 Enave-T 550 V A21 R	200	347	660	Right	A21	Optional	Optional	ModBus
 Enave-T 550 V A21 L	200	347	660	Left	A21	Optional	Optional	ModBus
 Enave 550 VE A21 R	200	347	660	Right	A21	Optional	Built-in	ModBus
 Enave 550 VE A21 L	200	347	660	Left	A21	Optional	Built-in	ModBus
 Enave-T 550 VE A21 R	200	347	660	Right	A21	Optional	Built-in	ModBus

	Enave-T 550 VE A21 L	200	347	660	Left	A21	Optional	Built-in	ModBus
	Enave 550 V A14 R	200	347	660	Right	A14			ModBus
	Enave 550 V A14 L	200	347	660	Left	A14			
	Enave-T 550 V A14 R	200	347	660	Right	A14			
	Enave-T 550 V A14 L	200	347	660	Left	A14			