






















Series **KSV**








Centrifugal fans in sound-insulated casing

- Sound insulation
- Motor type: AC
- Impeller type: Centrifugal backward curved blades
- Casing material: Coated steel
- Filter: G4+H13+Carbon



Lineup	Connected air duct size, mm	Rated power, W	Maximum airflow, m ³ /h
 KSV 100	100	53	190
 KSV 150	150	107	440
 KSV 150 Q	150	63	360
 KSV 200	200	123	580
 KSV 100 G4	100	53	190
 KSV 100 G4/Carbon	100	53	190
 KSV 100 G4/F8	100	53	180

 KSV 100 G4/F8/Carbon	100	53	180
 KSV 100 G4/H13	100	52	170
 KSV 100 G4/H13/Carbon	100	52	170
 KSV 150 G4	150	107	440
 KSV 150 G4/Carbon	150	107	440
 KSV 150 G4/F8	150	104	400
 KSV 150 G4/F8/Carbon	150	104	400
 KSV 150 G4/H13	150	102	360
 KSV 150 G4/H13/Carbon	150	102	360
 KSV 150 Q G4	150	63	360
 KSV 150 Q G4/Carbon	150	63	360
 KSV 150 Q G4/F8	150	61	330
 KSV 150 Q G4/F8/Carbon	150	61	330
 KSV 150 Q G4/H13	150	59	310

 KSV 150 Q G4/H13/Carbon	150	59	310
 KSV 200 G4	200	123	580
 KSV 200 G4/Carbon	200	123	580
 KSV 200 G4/F8	200	120	570
 KSV 200 G4/F8/Carbon	200	120	570
 KSV 200 G4/H13	200	115	490
 KSV 200 G4/H13/Carbon	200	115	490