

## Series **LD**



Axial decorative fans for exhaust ventilation

- Motor type: AC
- Casing material: Plastic
- Timer: Turn off timer
- Humidity sensor

Lineup	Connected air duct size, mm	Maximum airflow, m <sup>3</sup> /h	Sound pressure level LpA at 3 m, dB(A)	Pull cord	Humidity sensor	Timer	Electric power input, W
 100 LD	100	88	33	✗	✗	✗	14
 100 LD 12	100	77	32	✗	✗	✗	14
 100 LD Q	100	60	25	✗	✗	✗	5.5
 100 LD turbo	100	115	36	✗	✗	✗	16
 100 LD V	100	88	33	✓	✗	✗	14
 100 LD VT	100	88	33	✓	✗	✓	14

 100 LD V 12	100	77	32	✓	✗	✗	14
 100 LD L Q	100	60	25	✗	✗	✗	0
 100 LD VTH	100	88	33	✓	✓	✓	14
 100 LD V L turbo	100	115	36	✓	✗	✗	0
 100 LD L turbo	100	115	36	✗	✗	✗	0
 100 LD K turbo	100	115	36	✗	✗	✗	0
 100 LD K L	100	88	33	✗	✗	✗	14
 100 LD L	100	88	33	✗	✗	✗	14
 100 LD TH L turbo	100	115	36	✗	✓	✓	16
 100 LD T L	100	88	33	✗	✗	✓	14
 100 LD TH L Q	100	60	25	✗	✓	✓	5.5
 100 LD T L turbo	100	115	36	✗	✗	✓	16
 100 LD K	100	88	33	✗	✗	✗	14
 100 LD TH L	100	88	33	✗	✓	✓	14

 100 LD T	100	88	33	×	×	✓	14
 100 LD T Q	100	60	25	×	×	✓	5.5
 100 LD T K	100	88	33	×	×	✓	14
 100 LD T K L	100	88	33	×	×	✓	14
 100 LD T K L Q	100	60	25	×	×	✓	5.5
 100 LD T L Q	100	60	25	×	×	✓	5.5
 100 LD T turbo	100	115	36	×	×	✓	16
 100 LD TH	100	88	33	×	✓	✓	14
 100 LD TH Q	100	60	25	×	✓	✓	5.5
 100 LD TH K	100	88	33	×	✓	✓	14
 100 LD TH K L	100	88	33	×	✓	✓	14
 100 LD TH turbo	100	115	36	×	✓	✓	16
 100 LD T 12	100	77	32	×	×	✓	14
 100 LD TH 12	100	77	32	×	✓	✓	14

 120 LD	120	161	34	×	×	×	
 125 LD turbo	125	209	36	×	×	×	24
 125 LD 12	125	149	33	×	×	×	16
 125 LD Q	125	108	31	×	×	×	9.3
 125 LD	125	167	34	×	×	×	16
 125 LD V	125	167	34	✓	×	×	16
 125 LD VT	125	167	34	✓	×	✓	16
 125 LD VTH	125	167	34	✓	✓	✓	16
 125 LD K	125	167	34	×	×	×	0
 125 LD K L	125	167	34	×	×	×	0
 125 LD L	125	167	34	×	×	×	0
 125 LD T	125	167	34	×	×	✓	16
 125 LD TH	125	167	34	×	✓	✓	16
 125 LD TH K	125	167	34	×	✓	✓	16

 125 LD T L	125	167	34	×	×	✓	16
 125 LD TH L	125	167	34	×	✓	✓	16
 125 LD TH K L	125	167	34	×	✓	✓	16
 125 LD K turbo	125	209	36	×	×	×	24
 125 LD L turbo	125	209	36	×	×	×	24
 125 LD T turbo	125	209	36	×	×	✓	24
 125 LD T K turbo	125	209	36	×	×	✓	24
 125 LD TH K turbo	125	209	36	×	✓	✓	24
 125 LD V L turbo	125	209	36	✓	×	×	24
 125 LD TH L turbo	125	209	36	×	✓	✓	24
 125 LD TH turbo	125	209	36	×	✓	✓	24
 125 LD T L turbo	125	209	36	×	×	✓	24
 100 LD K 12	100	77	32	×	×	×	14
 125 LD T 12	125	149	33	×	×	✓	16

 125 LD V 12	125	149	33	✓	✗	✗	16
 150 LD	150	265	37	✗	✗	✗	24
 150 LD V	150	265	37	✓	✗	✗	24
 150 LD VTH	150	265	37	✓	✓	✗	24
 150 LD K	150	265	37	✗	✗	✗	0
 150 LD K L	150	265	37	✗	✗	✗	0
 150 LD L	150	265	37	✗	✗	✗	0
 150 LD T	150	265	37	✗	✗	✓	24
 150 LD T K	150	265	37	✗	✗	✓	0
 150 LD T L	150	265	37	✗	✗	✓	0
 150 LD TH	150	265	37	✗	✓	✓	24
 150 LD TH K	150	265	37	✗	✓	✓	0
 150 LD TH L	150	265	37	✗	✓	✓	0
 150 LD turbo	150	310	39	✗	✗	✗	29

 150 LD L turbo	150	310	39	×	×	×	0
 150 LD T L turbo	150	310	39	×	×	✓	0
 150 LD V L turbo	150	310	39	✓	×	×	29
 150 LD TH turbo	150	310	39	×	✓	✓	29
 125 LD TH 12	125	149	33	×	✓	✓	16
 150 LD 12	150	236	36	×	×	×	29
 150 LD TH 12	150	236	36	×	✓	✓	29
 150 LD T 12	150	236	36	×	×	✓	29