









Series Micra 100



Basic compact wall AHU with an air flow of up to 100 m³/h

- Heat recovery efficiency: 96
- Heat exchanger type: Counter flow
- Sound insulation
- Motor type: EC
- Bypass: Auto
- Control: Built-in control panel
- Casing material: Coated steel
- Enthalpy heat exchanger
- Reheater: Electric
- Preheater: Electric

Lineup	Rated power, W	Maximum airflow, m ³ /h	Sound pressure level LpA at 3 m, dB(A)	Heat recovery efficiency, max, %	Enthalpy heat exchanger	Reheater	Preheater	Control	Mounting type
 Micra 100	45	100	39	98	✗	✗	✗	Built-in control panel	Wall
 Micra 100 ERV	45	100	39		✓	✗	✗	Built-in control panel	Wall
 Micra 100 E	45	100	39	98	✗	Electric	✗	Built-in control panel	Wall
 Micra 100 E ERV	45	100	39		✓	Electric	✗	Built-in control panel	Wall
 Micra 100 E1	45	100	39		✗	✗	Electric	Built-in control panel	Wall
 Micra 100 E1 ERV	45	100	39		✓	✗	Electric	Built-in control panel	Wall

	Micra 100 E2	45	100	39		✘	Electric	Electric	Built-in control panel	Wall
	Micra 100 E2 ERV	45	100	39		✔	Electric	Electric	Built-in control panel	Wall