

















## Series S



Axial fans for exhaust ventilation

- Motor type: AC
- Casing material: Polypropylene/Thermoplastic elastomer
- Timer: Turn off timer
- Humidity sensor

Lineup	Connected air duct size, mm	Rated power, W	Maximum airflow, m <sup>3</sup> /h	Sound pressure level LpA at 3 m, dB(A)	Pull cord	Humidity sensor	Timer
 100 S	100	14	95	34	✗	✗	✗
 100 S K	100	14	95	34	✗	✗	✗
 100 S T	100	14	95	34	✗	✗	✓
 100 S T L	100	14	95	34	✗	✗	✓
 100 S L	100	14	95	34	✗	✗	✗
 100 S V	100	14	95	34	✓	✗	✗

 100 S VL	100	14	95	34	✓	✗	✗
 100 S TH L	100	14	95	34	✗	✓	✓
 100 S 12	100	14	86	33	✗	✗	✗
 100 S turbo	100	16	124	37	✗	✗	✗
 125 S	125	16	180	35	✗	✗	✗
 125 S turbo	125	24	226	37	✗	✗	✗
 125 S 12	125	16	165	34	✗	✗	✗
 150 S	150	24	292	38	✗	✗	✗
 150 S turbo	150	30	341	40	✗	✗	✗
 150 S 12	150	24	260	37	✗	✗	✗