







## Series **Silenta-S**











Low noise and low watt axial fans for exhaust ventilation

- Motor type: AC
- Impeller type: Axial
- Casing material: Plastic
- Timer: Turn off timer
- Humidity sensor

Lineup	Connected air duct size, mm	Maximum airflow, m <sup>3</sup> /h	Sound pressure level LpA at 3 m, dB(A)	Timer	Humidity sensor	Pull cord
 100 Silenta-S	100	78	26			
 100 Silenta-S L	100	78	26			
 100 Silenta-S K	100	78	26			
 100 Silenta-ST	100	78	26	✓		
 125 Silenta-S	125	148	31			
 100 Silenta-STH	100	78	26	✓	✓	

 125 Silenta-S K	125	148	31			
 125 Silenta-S L	125	148	31			
 125 Silenta-ST	125	148	31	✓		
 125 Silenta-STH	125	148	31	✓	✓	
 125 Silenta-SV	125	148	31			✓
 125 Silenta-SVT	125	148	31	✓		✓
 125 Silenta-SVTH	125	148	31	✓	✓	✓
 150 Silenta-S	150	240	33			
 150 Silenta-S K	150	240	33			
 150 Silenta-S L	150	240	33			
 100 Silenta-SV	100	78	26			✓
 150 Silenta-ST	150	240	33	✓		
 150 Silenta-STH	150	240	33	✓	✓	
 150 Silenta-SV	150	240	33			✓

 150 Silenta-SVT	150	240	33	✓		✓
 150 Silenta-SVTH	150	240	33	✓	✓	✓
 150 Silenta-S (220 V/60 Hz)	150					
 100 Silenta-SVT	100	78	26	✓		✓
 150 Silenta-S K (220 V/60 Hz)	150					
 150 Silenta-S L (220 V/60 Hz)	150					
 150 Silenta-ST (220 V/60 Hz)	150			✓		
 150 Silenta-STH (220 V/60 Hz)	150			✓	✓	
 150 Silenta-SV (220 V/60 Hz)	150					✓
 150 Silenta-SVT (220 V/60 Hz)	150			✓		✓
 150 Silenta-SVTH (220 V/60 Hz)	150			✓	✓	✓
 100 Silenta-SVTH	100	78	26	✓	✓	✓