





















Series Simple









Axial extract fans with thin front panels

- Motor type: AC
- Casing material: Polypropylene/Thermoplastic elastomer
- Humidity sensor
- Timer: Turn off timer

Lineup	Connected air duct size, mm	Rated power, W	Maximum airflow, m ³ /h	Sound pressure level LpA at 3 m, dB(A)	Pull cord	Humidity sensor	Timer
 100 Simple	100	14	95	34	×	×	×
 100 Simple turbo	100	16	124	37	×	×	×
 100 Simple Q1	100	8	85	28	×	×	×
 100 Simple K	100	14	95	34	×	×	×
 100 Simple K L Q1	100	8	85	28	×	×	×
 100 Simple T	100	14	95	34	×	×	×

 100 Simple T K L Q1	100	8	85	28	✗	✗	✗
 100 Simple T turbo	100	16	124	37	✗	✗	✗
 100 Simple TH	100	14	95	34	✗	✓	✓
 100 Simple TH K L Q1	100	8	85	28	✗	✓	✓
 120 Simple	120	16	174	35	✗	✗	✗
 120 Simple Q1	120	10	162	32	✗	✗	✗
 120 Simple K L Q1	120	10	162	32	✗	✗	✗
 120 Simple T	120	16	174	35	✗	✗	✓
 120 Simple turbo	120	24	219	37	✗	✗	✗
 120 Simple T K L Q1	120	10	162	32	✗	✗	✓
 120 Simple T turbo	120	24	219	37	✗	✗	✓
 120 Simple TH	120	16	174	35	✗	✓	✓
 125 Simple	125	16	180	35	✗	✗	✗
 125 Simple turbo	125	24	226	37	✗	✗	✗

 125 Simple T turbo	125	24	226	37	✗	✗	✗
 125 Simple TH	125	16	180	35	✗	✓	✗
 125 Simple TH turbo	125	24	226	37	✗	✓	✗
 150 Simple	150	25	280	34	✗	✗	✗
 150 Simple V	150	25	280	34	✓	✗	✗
 150 Simple T	150	25	280	34	✗	✗	✓