





















Series **Simple**









Axial fans for exhaust ventilation

- Motor type: AC
- Casing material: Plastic
- Humidity sensor
- Timer: Turn off timer

Lineup	Connected air duct size, mm	Maximum airflow, m ³ /h	Sound pressure level LpA at 3 m, dB(A)	Pull cord	Humidity sensor	Timer	Electric power input, W
 100 Simple	100	95	34	×	×	×	14
 100 Simple turbo	100	124	37	×	×	×	16
 100 Simple Q1	100	85	28	×	×	×	8
 100 Simple K	100	95	34	×	×	×	
 100 Simple K L Q1	100	85	28	×	×	×	
 100 Simple T	100	95	34	×	×	×	14

 100 Simple T K L Q1	100	85	28	×	×	×	
 100 Simple T turbo	100	124	37	×	×	×	16
 100 Simple TH	100	95	34	×	✓	✓	14
 100 Simple TH K L Q1	100	85	28	×	✓	✓	
 120 Simple	120	174	35	×	×	×	16
 120 Simple Q1	120	162	32	×	×	×	10
 120 Simple K L Q1	120	162	32	×	×	×	
 120 Simple T	120	174	35	×	×	✓	16
 120 Simple turbo	120	219	37	×	×	×	24
 120 Simple T K L Q1	120	162	32	×	×	✓	
 120 Simple T turbo	120	219	37	×	×	✓	24
 120 Simple TH	120	174	35	×	✓	✓	16
 125 Simple	125	180	35	×	×	×	16
 125 Simple turbo	125	226	37	×	×	×	24

 125 Simple T turbo	125	226	37	✗	✗	✗	24
 125 Simple TH	125	180	35	✗	✓	✗	16
 125 Simple TH turbo	125	226	37	✗	✓	✗	24
 150 Simple	150	280	34	✗	✗	✗	25
 150 Simple V	150	280	34	✓	✗	✗	25
 150 Simple T	150	280	34	✗	✗	✓	25