







Series **Solid**



Low-noise and low-power extract axial fan with air flow up to 155 m³/h

- Motor type: AC
- Casing material: Plastic
- Timer: Turn off timer
- Humidity sensor

Lineup	Connected air duct size, mm	Maximum airflow, m ³ /h	Sound pressure level LpA at 3 m, dB(A)	Pull cord	Humidity sensor	Timer	Electric power input, W
 100 Solid	100	85	27	×	×	×	8
 100 Solid Alu	100	85	27	×	×	×	
 100 Solid Beige	100	85	27	×	×	×	
 100 Solid Black Sapphire	100	85	27	×	×	×	
 100 Solid Red	100	85	27	×	×	×	
 100 Solid L	100	85	27	×	×	×	

	100 Solid L Black Sapphire	100	85	27	✗	✗	✗	
	100 Solid L K	100	85	27	✗	✗	✗	
	100 Solid T	100	85	27	✗	✗	✓	8
	100 Solid T Black Sapphire	100	85	27	✗	✗	✓	
	100 Solid T L	100	85	27	✗	✗	✓	
	100 Solid TH	100	85	27	✗	✓	✓	8
	100 Solid TH Black Sapphire	100	85	27	✗	✗	✓	
	100 Solid Alu T	100	85	27	✗	✗	✓	
	100 Solid Alu TH	100	85	27	✗	✓	✓	
	100 Solid TH L	100	85	27	✗	✗	✓	
	100 Solid TH L K	100	85	27	✗	✗	✓	
	100 Solid V	100	85	27	✓	✗	✗	8
	100 Solid VTH	100	85	27	✓	✓	✓	8
	125 Solid	125	155	32	✗	✗	✗	18

 125 Solid Alu	125	155	32	✗	✗	✗	
 125 Solid Black Sapphire	125	155	32	✗	✗	✗	
 125 Solid Red	125	155	32	✗	✗	✗	
 125 Solid T	125	155	32	✗	✗	✓	18
 125 Solid T Black Sapphire	125	155	32	✗	✗	✓	
 125 Solid T1	125	155	32	✗	✗	✓	18
 125 Solid T L	125	155	32	✗	✗	✓	
 125 Solid TH	125	155	32	✗	✓	✓	18
 125 Solid TH Black Sapphire	125	155	32	✗	✓	✓	
 125 Solid TH L	125	155	32	✗	✓	✓	