







Series **Solid**



Low-noise and low-power extract axial fan with air flow up to 155 m³/h

- Motor type: AC
- Casing material: Plastic
- Timer: Turn off timer
- Humidity sensor

Lineup	Connected air duct size, mm	Rated power, W	Maximum airflow, m ³ /h	Sound pressure level LpA at 3 m, dB(A)	Pull cord	Humidity sensor	Timer
 100 Solid	100	8	85	27	×	×	
 100 Solid Alu	100	8	85	27	×	×	
 100 Solid Beige	100	8	85	27	×	×	
 100 Solid Black Sapphire	100	8	85	27	×	×	
 100 Solid Red	100	8	85	27	×	×	
 100 Solid L	100	8	85	27	×	×	

	100 Solid L Black Sapphire	100	8	85	27	×	×	
	100 Solid L K	100	8	85	27	×	×	
	100 Solid T	100	8	85	27	×	×	✓
	100 Solid T Black Sapphire	100	8	85	27	×	×	✓
	100 Solid T L	100	8	85	27	×	×	✓
	100 Solid TH	100	8	85	27	×	✓	✓
	100 Solid TH Black Sapphire	100	8	85	27	×	×	✓
	100 Solid Alu T	100	8	85	27	×	×	✓
	100 Solid Alu TH	100	8	85	27	×	✓	✓
	100 Solid TH L	100	8	85	27	×	×	✓
	100 Solid TH L K	100	8	85	27	×	×	✓
	100 Solid V	100	8	85	27	✓	×	×
	100 Solid VTH	100	8	85	27	✓	✓	✓
	125 Solid	125	18	155	32	×	×	×

 125 Solid Alu	125	18	155	32	×	×	×
 125 Solid Black Sapphire	125	18	155	32	×	×	×
 125 Solid Red	125	18	155	32	×	×	×
 125 Solid T	125	18	155	32	×	×	✓
 125 Solid T Black Sapphire	125	18	155	32	×	×	✓
 125 Solid T1	125	18	155	32	×	×	✓
 125 Solid T L	125	18	155	32	×	×	✓
 125 Solid TH	125	18	155	32	×	✓	✓
 125 Solid TH Black Sapphire	125	18	155	32	×	✓	✓
 125 Solid TH L	125	18	155	32	×	✓	✓